

Is my new antifouling compatible?

Once you've identified the International antifouling that's most suitable, if you have an existing coating on your hull you will need to establish the compatibility of the two products. Use this simple table to check compatibility between International® antifoulings.

		New Antifouling						
		Awlcraft	Micron® Extra 2 Micron® Extra Micron® 66 Micron® 77	Ultra Ultra 2	Trilux® 33	Bottomkote	VC® Offshore	
Existing Antifouling (in good condition)	Micron® Extra Micron® Extra 2 Awlcraft	●	●	●	●	●	●	
	Bottomkote	●	●	●	●	●	●	
	Trilux® 33 VC® Offshore Ultra Ultra 2	●	●	●	●	●	●	
	Unknown Product	●	●	●	●	●	●	
	Previous antifouling in poor condition	●	●	●	●	●	●	



● Apply after a light wet sand. Wash with fresh water and allow to dry.

● Remove the antifouling.

● Apply a barrier coat of Primocon before applying antifouling.

Australia & Pacific Islands

Akzo Nobel Pty Ltd, Unit 54/53, 76 Waterway Drive, Coomera, Queensland 4209

Tel: 61 (0) 7 5573 9600 Fax: 61 (0) 7 5573 9677 Technical Helpline: 1800 251 431 Email: tech.support@akzonobel.com

New Zealand

International Paint, 686 Rosebank Road, PO Box 19995, Avondale, Auckland 7

Tel: 64 (9) 828 3009 Fax: 64 (9) 828 1129 Technical Helpline: 0800 808 807 Email: technz.support@akzonobel.com

Asia

International Paint Singapore (Pte) Ltd., 3 Neythal Road, Singapore 628570

Tel: +65 (0) 6 261 5033 Fax: +65 (0) 6 862 0778 Technical Helpline: +65 (0) 6 261 5033 Email: yacht.asia@akzonobel.com

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2016.