

# Teak Oil

## Boatcare

Penetrating oil for protection of hardwood



### PRODUCT DESCRIPTION

Teak Oil is a special penetrating oil for protection of teak decks and teak interiors. It produces a protective and easy-clean surface.

- \* Traditional Scandinavian formula, containing linseed and tung oils, for ultimate protection
- \* For use on any interior or exterior hardwood
- \* Produces attractive sheen finish
- \* Penetrates even moist wood
- \* Contains a rust inhibitor for metal surfaces

### PRODUCT INFORMATION

<b>Colour</b>	YMB845
<b>Specific Gravity</b>	0.8
<b>Volume Solids</b>	33%
<b>Typical Shelf Life</b>	2 yrs
<b>VOC (As Supplied)</b>	552 g/lit
<b>Unit Size</b>	500 ml, 4 Lt

Not all pack sizes are available in all countries.

### DRYING/OVERCOATING INFORMATION

#### Drying

#### Overcoating

##### Substrate Temperature

Overcoated By	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
	Min	Max	Min	Max	Min	Max	Min	Max

### APPLICATION AND USE

<b>Preparation</b>	Ensure bare wood is clean and dry. Clean wood with Teak Restorer if required.
<b>Method</b>	Apply 1-2 coats of Teak Oil with a cloth or brush. Let the oil dry before touching. Repeat during the season if required. Remove teak oil from sealant as it could soften the sealant when left on for extended periods of time.
<b>Hints</b>	<b>Mixing</b> Shake well before use.
<b>Some Important Points</b>	Product temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Ambient temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Substrate temperature should be minimum 5°C/41°F and maximum 35°C/95°F.
<b>Compatibility/Substrates</b>	Suitable for use on interior or exterior hardwood.
<b>Application Methods</b>	Brush, cloth

### TRANSPORTATION, STORAGE AND SAFETY INFORMATION

<b>Storage</b>	<b>GENERAL INFORMATION:</b> Exposure to air and extremes of temperature should be avoided. For the full shelf life of Teak Oil to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight. <b>TRANSPORTATION:</b> Teak Oil should be kept in securely closed containers during transport and storage.
<b>Safety</b>	<b>GENERAL:</b> Read the label safety section for Health and Safety Information, also available from our Technical Help Line. <b>DISPOSAL:</b> Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Remainders of Teak Oil cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.

### IMPORTANT NOTES

*The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to*

Please refer to your local representative or visit [www.yachtpaint.com](http://www.yachtpaint.com) for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2015.

Teak Oil

Boatcare

Penetrating oil for protection of hardwood



---

*modification from time to time in the light of experience and our policy of continuous product development.*

---

Please refer to your local representative or visit [www.yachtpaint.com](http://www.yachtpaint.com) for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2015.

Ref:3518 Teak Oil Issue Date:30/10/2015