

PRODUCT DESCRIPTION

UV Wax Sealer is a high performance, deep-gloss wax sealer. It is a non-abrasive reactive wax sealing solution with a fluoro micro additive. Provides excellent protection against dirt and oil contamination.

- * Use with Marine Polish for the longest-lasting ultimate protection
- * Thin film reactive formula provides the ultimate UV protection
- * May be left for an extended period prior to polishing off
- * Machine polishable
- * Provides long-lasting, high gloss, hard-shell protection
- * May be used in direct sunlight
- * Produces dirt-repellant, easy to clean surface
- * Also suitable for use on the car, caravan or garden furniture

PRODUCT INFORMATION

Colour	YMB839
Specific Gravity	0.76
Volume Solids	5%
Typical Shelf Life	2 yrs
VOC (As Supplied)	729 g/lt
Unit Size	500 ml

DRYING/OVERCOATING INFORMATION

Drying

Overcoating

Substrate Temperature

	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
Overcoated By	Min	Max	Min	Max	Min	Max	Min	Max

APPLICATION AND USE

Preparation	Clean the surface with Super Cleaner and fresh water. Allow to dry. To achieve the best results, pretreat the surface with Marine Polish.
Method	Apply a thin layer of UV Wax Sealer with a clean dry cloth. Allow to dry. Polish out to a high gloss using a cloth or machine. Change cloths frequently.
Hints	Mixing - Shake well before use.
Some Important Points	Product temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Ambient temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Substrate temperature should be minimum 5°C/41°F and maximum 35°C/95°F.
Compatibility/Substrates	Suitable for use on GRP and painted surfaces.
Application Methods	Cloth or machine.

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage	GENERAL INFORMATION: Exposure to air and extremes of temperature should be avoided. For the full shelf life of this product to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight. TRANSPORTATION: UV Wax Sealer should be kept in securely closed containers during transport and storage.
Safety	GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line.

Please refer to your local representative or visit www.yachtpaint.com for further information.

 International, the AkzoNobel logo and other products mentioned are trademarks of AkzoNobel. © AkzoNobel 2013.



DISPOSAL:

Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal.

Remainders of UV Wax Sealer cannot be disposed of through the municipal waste route or dumped without permit.

Disposal of remainders must be arranged for in consultation with the authorities.

IMPORTANT NOTES

The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.