

ANTIFOULING COMPATIBILITY CHART

CHOSEN ANTIFOULING		MICRON® OPTIMA	MICRON® EXTRA	INTERSPEED ULTRA	CRUISER® UNO	TRILUX	NAVIGATOR	BOTTOMCOAT	VC® 17m EXTRA	VC® OFFSHORE WITH TEFLON®	TRILUX PROP-O-DREV
PREVIOUS ANTIFOULING (IN GOOD CONDITION)	MICRON® OPTIMA	●	●	●	●	●	●	●	∅	●	●
	MICRON® EXTRA CRUISER® UNO WATERWAYS PLUS NAVIGATOR	●	●	●	●	●	●	●	∅	●	●
	TRILUX VC® OFFSHORE WITH TEFLON® INTERSPEED ULTRA	●	●	●	●	●	●	●	●	●	●
	VC® 17m EXTRA	∅	∅	∅	∅	∅	∅	∅	●	●	●
	UNKNOWN PRODUCT	B	B	B	B	B	B	B	∅	B	B
	PREVIOUS ANTIFOULING IN POOR CONDITION	∅	∅	∅	∅	∅	∅	∅	∅	∅	∅
	BLAKES TIGER	B	●	●	●	●	●	●	∅	●	●
	BLAKES HARD RACING	B	●	●	●	●	●	●	∅	●	●
	AWLGRIP® AWLSTAR GOLD LABEL	●	●	●	●	●	●	●	∅	●	●
	JOTUN NON STOP	●	●	●	●	●	●	●	∅	●	●
	JOTUN RACING	●	●	●	●	●	●	●	∅	●	●

KEY: ● Apply the chosen antifouling directly after a light wet sand, wash with fresh water and allow to dry.

∅ Remove the antifouling totally using Interstrip.

B Apply a barrier coat of Primocon® before applying the chosen antifouling.