

COVERAGE CHART

ANTIFOULING		
PRODUCT	COVERAGE PER GALLON	NUMBER OF COATS
MICRON® 66®	320 SQ FT/GAL YIELDS 2 MILS D.F.T.	2-3
MICRON® EXTRA WITH BIOLUX®	440 SQ FT/GAL YIELDS 2 MILS D.F.T.	2-3
MICRON® CSC	440 SQ FT/GAL YIELDS 2 MILS D.F.T.	2-3
FIBERGLASS BOTTOMKOTE® ACT	400 SQ FT/GAL YIELDS 2 MILS D.F.T.	2-3
ULTRA WITH BIOLUX®	475 SQ FT/GAL YIELDS 2 MILS D.F.T.	2
ULTRA-KOTE®	475 SQ FT/GAL YIELDS 2 MILS D.F.T.	2
FIBERGLASS BOTTOMKOTE®	400 SQ FT/GAL YIELDS 2 MILS D.F.T.	2
FIBERGLASS BOTTOMKOTE® AQUA	400 SQ FT/GAL YIELDS 2 MILS D.F.T.	2
TRILUX® 33®	400 SQ FT/GAL YIELDS 2 MILS D.F.T.	2-3
TRI-LUX® II	400 SQ FT/GAL YIELDS 2 MILS D.F.T.	2-3
TRILUX® PROP & DRIVE		1 CAN PER LOWER UNIT
BOTTOMKOTE®	400 SQ FT/GAL YIELDS 2 MILS D.F.T.	2-3
BOTTOMKOTE® XXX	420 SQ FT/GAL YIELDS 2 MILS D.F.T.	2-3
VC*17m & VC*17m EXTRA	300 SQ FT/GAL YIELDS 4.2 MILS D.F.T.	2
GELCOAT BLISTER PROTECTION		
INTERPROTECT® 2000E	240 SQ FT/GAL YIELDS 2.7 MILS D.F.T.	4-5*
INTERPROTECT® 3000	330 SQ FT/GAL YIELDS 3.8 MILS D.F.T.	3-4*
VC® TAR2	280 SQ FT/GAL YIELDS 4 MILS D.F.T.	4-5*
EPIGLASS® HT9000 RESIN	400 SQ FT/GAL YIELDS 4 MILS D.F.T.	2-3 AS NEEDED
PRIMERS		
TBT SEALER	264 SQ FT/GAL YIELDS 2 MILS D.F.T.	2
PRIMOCON	210 SQ FT/GAL YIELDS 2 MILS D.F.T.	2
VINY-LUX PRIMEWASH	425 SQ FT/GAL YIELDS 8 MILS D.F.T.	1-2
PRE-KOTE	450 SQ FT/GAL YIELDS 2 MILS D.F.T.	1-2
EPOXY PRIMEKOTE®	450 SQ FT/GAL YIELDS 2 MILS D.F.T.	1-2
TOPSIDE FINISHES		
PERFECTION® POLYURETHANE	535 SQ FT/GAL YIELDS 1.5 MILS D.F.T.	2-3 AS NEEDED
TOPLAC	550 SQ FT/GAL YIELDS 1.2 MILS D.F.T.	2-3 AS NEEDED
BRIGHTSIDE® POLYURETHANE	550 SQ FT/GAL YIELDS 1.2 MILS D.F.T.	2-3 AS NEEDED
BILGEKOTE®	300 SQ FT/GAL YIELDS 1.2 MILS D.F.T.	2-3 AS NEEDED
VARNISHES		
PERFECTION®	525 SQ FT/GAL YIELDS 2 MILS D.F.T.	4-5 AS NEEDED
SCHOONER®	600 SQ FT/GAL YIELDS 2 MILS D.F.T.	4-5 AS NEEDED
GOLDSPAR® CLEAR	600 SQ FT/GAL YIELDS 2 MILS D.F.T.	4-5 AS NEEDED
GOLDSPAR® SATIN	600 SQ FT/GAL YIELDS 2 MILS D.F.T.	4-5 AS NEEDED
ORIGINAL	600 SQ FT/GAL YIELDS 2 MILS D.F.T.	4-5 AS NEEDED
JET SPEED	640 SQ FT/GAL YIELDS 2 MILS D.F.T.	2
FILLERS		
INTERFILL® EPOXY FILLER	25 SQ FT/GAL YIELDS 1/16" D.F.T.	AS NEEDED
WATERTITE EPOXY FILLER	25 SQ FT/GAL YIELDS 1/16" D.F.T.	AS NEEDED
SURFACING PUTTY	60 SQ FT/GAL YIELDS 1/16" D.F.T.	AS NEEDED
BOATYARD BEDDING COMPOUND	25 SQ FT/GAL YIELDS 1/16" D.F.T.	AS NEEDED
SEAM COMPOUND BROWN / WHITE	25 SQ FT/GAL YIELDS 1/16" D.F.T.	AS NEEDED

D.F.T. – Dry Film Thickness

Coverages are theoretical your coverage may vary

1 mil = 1/1000th of an inch

25.4 microns = 1 mil